Slitting and cut-to-length line TwinCut 20

Model	TwinCut 20
Brand	EKICONTROL
Condition	new
Origin	Spain

approx. 6 months from order

Price on request







General characteristics

Dimensions and weight

Description

Standard equipment

• Uncoiler

• Coil car

• Pneumatic input table

• Entry guide

Hesse + Co Maschinenfabrik GmbH
IZ Nö Süd, Straße 4, Objekt 8
A-2351 Wiener Neudorf
www.hesse-maschinen.com
T +43-2236-63870-0
F +43-2236-63662
office@hesse-maschinen.com

• 7 Straightening rolls

• Slitting shaft with 3 sets of quickly adjustable circular blades

• Cut-to-length shears

• Servomotor

Options

• Hydraulic input table

• Film plastic device

• Scrap rewinders

• Additional circular blades

• Stacking tables

• Packers

Model:	Width to process:	Cutting thickness (mm):	Coil weight (kg)	Number of straightening rolls:	Cutting accuracy:	Number of straightening rolls:	Production speed:
TwinCut 20 **DM6**	1000	0`5 - 2	6.000	3 - 6	+/– 0`5 mm	2 + 7	20 m/min
TwinCut 20 **DM10**	1250		10.000				
TwinCut 20 **DM15**	1500		15.000				

Material to be processed:	**Thickness:**	**N of simultaneous cuts:**
Steel 420 Nw/mm2	2`00 mm	3
	1`50 mm	4
	0`50 mm	6
Steel 700 Nw/mm2	1`25 mm	3
	1`00 mm	4
	0`50 mm	6
Steel 200 Nw/mm2	4`00 mm	3
	2`00 mm	5
	1`00 mm	6

If you are interested, please send us your enquiry with the following details:

Coil weight

Coil width

Coil inner and outer diameter

type of material

Material thickness

Number of slitting lines (only for slitting and cut-to-length lines)

Material to be processed in tonnes per year

Further information

Brochures

- EKICONTROL Catalogue 2024 english

Product video

- snvejkofxgo.youtube

Notice

Prices ex location, excluding VAT.

The General Terms and Conditions of Delivery of the Austrian Association of the Machine and Steel Construction Industry apply.

We only sell under retention of title, the goods remain our unrestricted property until they have been paid for in full.

Price changes and errors excepted.