

Slitting and cut-to-length line XS LINE 1250

Model	XS LINE 1250
Brand	<u>EKICONTROL</u>
Condition	new
Origin	Spain

🕒 approx. 6 months from order

Price on request



General characteristics

Dimensions and weight

Description

Standard equipment

- Entry guide
- 2 Feeding rolls
- 5 Straightening rolls
- Cut-to-length shears
- Encoder
- Touch screen control
- Servomotor
- Slitting shaft with 2 sets of quickly adjustable circular blades, to a maximum of 6 blades

Options

- Film plastic device

- Different types of uncoilers
- Stacking systems
- Recoiler

Maximum Width:

MateThic Num Prod Coil I Num Strai SheaDime
rial t knes ber ouctiooadi ber oghte rs Ponsio
o be s: f sim n sp ng c f straning wer: ns:
proc ultaneed: apac ighteServ
esse eous ity: ning oMot
d: slitti rolls:or:
ng c
uts:

1250 Steel1`25 2 from 2 + 15 k 3 kW2100
420 mm 0 zu 5 W x 17
Nw/ 1`00 4 120 3, 6, 00 x
mm2mm Mete10 to 1450
0`50 6 r pro mm
mm Minu 2500
Steel0`75 2 te kg
700 mm
Nw/ 0`50 4
mm2mm
Alum2`50 2
iniu mm
m 201`50
0 Nwmm
/mm 1`00 6
2 mm

If you are interested, please send us your enquiry with the following details:

- Coil weight
- Coil width
- Coil inner and outer diameter
- type of material
- Material thickness
- Number of slitting lines (only for slitting and cut-to-length lines)
- Material to be processed in tonnes per year

Further information

Brochures

- [EKICONTROL Catalogue 2024 english](#)

Product video

- [dgzy2cxabek.youtube](https://www.youtube.com/watch?v=dgzy2cxabek)

Notice

Prices ex location, excluding VAT.

The [General Terms and Conditions of Delivery](#) of the Austrian Association of the Machine and Steel Construction Industry apply.

We only sell under retention of title, the goods remain our unrestricted property until they have been paid for in full.

Price changes and errors excepted.