Cross-cutting system ONECUT 20

Model	ONECUT 20
Brand	EKICONTROL
Condition	new
Origin	Spain

approx. 6 months from order

Price on request









General characteristics

Dimensions and weight

Hesse + Co Maschinenfabrik GmbH
IZ Nö Süd, Straße 4, Objekt 8
A-2351 Wiener Neudorf
www.hesse-maschinen.com
T +43-2236-63870-0
F +43-2236-63662
office@hesse-maschinen.com

Description

Standard equipment

• Entry guide

• Feeding rolls

• 7 Straightening rolls

• Encoder

• Shear

• Variable speed of 0 to 20 mts/min

Options

• Film plastic device

• Motorised entry guide

• Hydraulic entry table

• Hydraulic dauble entry table

• Stackers 2, 3, 4, 6 meters.

Material to be processed:	Width to process:	Thickness (R=450Nw/mm2)	Production speed:	Cutting accuracy:	Coil loading capacity:
Steel 420 Nw/mm2 Steel 700 Nw/mm2 Aluminium 200 Nw/mm2	750, 1000, 1250, 1500 mm	from 0`5 to 1`5 - 2`0 - 3`0 - 4`0 mm	up to 20 m/min	+/– 0`5 mm	4,6,10,15 to n

If you are interested, please send us your enquiry with the following details:

- Coil weight

- Coil width

- Coil inner and outer diameter

- type of material

- Material thickness

- Number of slitting lines (only for slitting and cut-to-length lines)

- Material to be processed in tonnes per year

Further information

Brochures

- EKICONTROL Catalogue 2024 english

Product video

- nblaqwj5wye.youtube

Notice

Prices ex location, excluding VAT.

The General Terms and Conditions of Delivery of the Austrian Association of the Machine and Steel Construction Industry apply.

We only sell under retention of title, the goods remain our unrestricted property until they have been paid for in full.

Price changes and errors excepted.