

Cross-cutting system ONECUT 20

Model	ONECUT 20
Brand	<u>EKICONTROL</u>
Condition	new
Origin	Spain

⌚ approx. 6 months from order

Price on request



General characteristics

Dimensions and weight

Description

Standard equipment

- Entry guide
- Feeding rolls
- 7 Straightening rolls
- Encoder
- Shear
- Variable speed of 0 to 20 mts/min

Options

- Film plastic device
- Motorised entry guide
- Hydraulic entry table
- Hydraulic double entry table
- Stackers 2, 3, 4, 6 meters.

Material to be processed:

Steel
420 Nw/mm²
Steel
700 Nw/mm²
Aluminium
200 Nw/mm²

Width to p rocess:	Thickness (R=450Nw/speed: mm ²)	Production speed:	Cutting ac curacy:	Coil loadin g capacity:
750,	from 0`5	up to 20 m/	+/- 0`5 m	4,6,10,15 to
1000,	to	min	m	
1250,	1`5 - 2`0 - 3			
1500 mm	`0 - 4`0 mm			

If you are interested, please send us your enquiry with the following details:

- Coil weight
- Coil width
- Coil inner and outer diameter
- type of material
- Material thickness
- Number of slitting lines (only for slitting and cut-to-length lines)
- Material to be processed in tonnes per year

Further information

Brochures

- [EKICONTROL Catalogue 2024 english](#)

Product video

- [nblaqwj5wye.youtube](https://www.youtube.com/watch?v=nblaqwj5wye)

Notice

Prices ex location, excluding VAT.

The [General Terms and Conditions of Delivery](#) of the Austrian Association of the Machine and Steel Construction Industry apply.

We only sell under retention of title, the goods remain our unrestricted property until they have been paid for in full.

Price changes and errors excepted.