

Fiber laser HD-FN 4020

Model	HD-FN 4020
Brand	<u>HESSE by DURMA</u>
Condition	new
Cutting area	4100 x 2070 mm
Laser power	3 kW
Origin	Türkiye

⌚ approx. 12 - 14 weeks from order

€ 230.188,00



General characteristics

Laser power	3 kW
Manual table / shuttle table	Shuttle table
Max. sheet thickness - mild steel	16 mm
Max. thickness - stainless steel	8 mm
Max. thickness - aluminium	8 mm
Max. Application Range - Copper	5 mm
Max. Application Range - Brass	8 mm
Total power	27,9 (mit Absaugung) kW
Cutting area	4100 x 2070 mm
X-axis	4100 mm
Y-axis	2070 mm
Z-Axis	125 mm
Max. Sheet size	4064 x 2032 mm
Max. sheet weight	240 (für 3 - 12 kW) / 400 (für 15 -20 kW) kg/m ²
Max. total weight for double table	3900 (für 3 - 12 kW) / 6400 (für 15 - 20 kW) kg
Max speed x-axes	100 m/min
Max speed y-axes	100 m/min
Max. speed simultaneous	141 m/min
Max. acceleration	14 m/s ²
Positioning accuracy	+/- 0,05 mm
Repeat accuracy	+/- 0,05 mm
Table change time	32 s

Dimensions and weight

Description

The HD-FN has two tables which are automatically switched alternately to enable simultaneous cutting and loading/unloading.

The shuttle table is positioned longitudinally, which results in the best possible accessibility for optional loading and unloading systems.

Control, laser source and cooling are integrated into the machine. The cutting head has automatic focus adjustment.

The system consists of the following components:

Shuttle table (positioned longitudinally for best possible accessibility for optional loading and unloading systems)

Encapsulated cutting room with protective glazing

CNC graphic control with touchscreen

Laser source Brilase Premium

Cutting head with automatic focus adjustment

Integrated cooling unit for cutting head and laser source

CAD/CAM software Lantek for programming including autonesting

Positioning laser

Sheet check system (automatic detection of sheet position and dimensions)

Automatic nozzle cleaning

Central lubrication

Slug box

Working area lighting

Multi-chamber suction system

Light barrier protection for the changing table

Remote maintenance access

Air condition for electrical cabinet

Equipped according to CE guidelines

Alternative laser sources:

Material	4 kW	6 kW	12 kW	15 kW	20 kW
Mild steel S235	20	25	30	35	40
Stainless steel (304)	10	15	25	35	40
Aluminium (5083)	12	20	30	35	40
Copper	6	10	15	15	15
Brass (CuZn39 Pb3)	10	12	20	20	20

Options:

Suction unit with filter
Sheet handling systems
Automatic nozzle change

Further information

Brochures

- [Katalog Laserschneidanlagen Durma](#)
- [HD-FN 4020 technical data sheet](#)

Notice

Prices ex location, excluding VAT.

The [General Terms and Conditions of Delivery](#) of the Austrian Association of the Machine and Steel Construction Industry apply.

We only sell under retention of title, the goods remain our unrestricted property until they have been paid for in full.

Price changes and errors excepted.