

Fiber laser HD-FN 3015

Model	HD-FN 3015
Brand	<u>HESSE by DURMA</u>
Condition	new
Cutting area	3100 x 1525 mm
Laser power	3 kW
Origin	Türkiye

🕒 approx. 12 - 14 weeks from order

€ 188.488,00

Leasing*: € 3.562,42



General characteristics

Laser power	3 kW
Manual table / shuttle table	Shuttle table
Max. sheet thickness - mild steel	16 mm
Max. thickness - stainless steel	8 mm
Max. thickness - aluminium	8 mm
Max. Application Range - Copper	5 mm
Max. Application Range - Brass	8 mm
Total power	26,4 (mit Absaugung) kW
Cutting area	3100 x 1525 mm
X-axis	3100 mm
Y-axis	1525 mm
Z-Axis	125 mm
Max. Sheet size	3084 x 1524 mm
Max. sheet weight	240 (für 3 - 12 kW) / 400 (für 15 - 20kW) kg/m ²
Max. total weight for double table	2200 (für 3 - 12kW) / 3600 (für 15 - 20kW) kg
Max speed x-axes	100 m/min
Max speed y-axes	100 m/min
Max. speed simultaneous	141 m/min
Max. acceleration	14 m/s ²
Positioning accuracy	+/- 0,05 mm
Repeat accuracy	+/- 0,05 mm

Table change time

25 s

Dimensions and weight

Description

The HD-FN has two tables which are automatically switched alternately to enable simultaneous cutting and loading/unloading.

The shuttle table is positioned longitudinally, which results in the best possible accessibility for optional loading and unloading systems.

Control, laser source and cooling are integrated into the machine. The cutting head has automatic focus adjustment.

The system consists of the following components:

Shuttle table (positioned longitudinally for best possible accessibility for optional loading and unloading systems)

Encapsulated cutting room with protective glazing

CNC graphic control with touchscreen

Laser source Brilase Premium

Cutting head with automatic focus adjustment

Integrated cooling unit for cutting head and laser source

CAD/CAM software Lantek for programming including autonesting

Positioning laser

Sheet check system (automatic detection of sheet position and dimensions)

Automatic nozzle cleaning

Central lubrication

Slug box

Working area lighting

Multi-chamber suction system

Light barrier protection for the changing table

Remote maintenance access

Air condition for electrical cabinet

Equipped according to CE guidelines

Alternative laser sources:

Material	4 kW	6 kW	12 kW	15 kW	20 kW
Mild steel S235	20	25	30	35	40
Stainless steel (304)	10	15	25	35	40
Aluminium (5083)	12	20	30	35	40
Copper	6	10	15	15	15

Brass (CuZn39 Pb3) 10 12 20 20 20

Options:

Suction unit with filter
Sheet handling systems
Automatic nozzle change

Further information

Brochures

- [HESSE by DURMA Laserkatalog 2025](#)
- [HD-FN 3015 technical data sheet](#)

Notice

Prices ex location, excluding VAT.

The [General Terms and Conditions of Delivery](#) of the Austrian Association of the Machine and Steel Construction Industry apply.

We only sell under retention of title, the goods remain our unrestricted property until they have been paid for in full.

Price changes and errors excepted.

* Monthly net leasing rate, leasing period 60 months, no down payment, 5% residual value, subject to a positive credit check. The leasing conditions of [GRENKELEASING GmbH](#) apply. Valid for lessees based in Austria.