

## Hydraulic plate shear SBT 4006

|                             |                       |
|-----------------------------|-----------------------|
| Model                       | SBT 4006              |
| Brand                       | <u>HESSE by DURMA</u> |
| Condition                   | new                   |
| Max. thickness - mild steel | 6 mm                  |
| Cutting length              | 4100 mm               |
| Origin                      | Türkiye               |

🕒 approx. 12 - 14 weeks from order

**€ 62.400,00**

Leasing\*: € 1.179,36



## General characteristics

|                                  |          |
|----------------------------------|----------|
| Cutting length                   | 4100 mm  |
| Max. thickness - mild steel      | 6 mm     |
| Max. thickness - stainless steel | 4 mm     |
| Gap in side frame                | 50 mm    |
| Strokes                          | 12 1/min |
| Cutting angle                    | 1.5 °    |
| Number of downholders            | 20 pcs.  |
| Pressure of downholder           | 17 to    |
| Back gauge                       | 1000 mm  |
| Back gauge speed                 | 200 mm/s |
| Motor power                      | 15 kW    |
| Oiltank                          | 200 l    |
| Support arms                     | 3 pcs.   |
| Table height                     | 865 mm   |
| Table width                      | 580 mm   |
| Table length                     | 4510 mm  |

## Dimensions and weight

|        |         |
|--------|---------|
| Length | 5230 mm |
|--------|---------|

|                                                   |          |
|---------------------------------------------------|----------|
| Width                                             | 2300 mm  |
| Total width with support arm und protection fence | 3600 mm  |
| Height                                            | 2150 mm  |
| Weight                                            | 11460 kg |

## Description

Swing cut construction

NC-preselection system D-touch 7 with touch screen for back gauge, cutting length, quantity, USB port

Motorized back gauge 1000 mm on ball screws, folding upwards

Clear control panel mounted on moveable arm

Hydraulic hold down pistons are arranged close to the cutting edge

Foot switch

Central, manual blade gap adjustment

Cutting line illumination

Broad table with balls

Piece counter

Single and continuous stroke

Fold up finger guard 1.000 mm

1 squaring arm 1. 500 mm with scale, T-slot and tilting cam

2 supporting arms 1.000 mm with T-slot

Simple replacement and grinding of the blades

Variable adjustable cutting length for economic processing

Lower blade fourfold turnable

Upper blade double turnable

Oilfilling

Light barrier on the back of the machine

Qualified customer support

User manual in GERMAN and ENGLISH

according to CE rules

(sample photo)

**We have more than 850 references!**

## Further information

### Brochures

- [Catalogue hydraulic plate shear Durma SBT series](#)

## Product video

- [vbmrudmw4du.youtube](https://vbmrudmw4du.youtube)

## Notice

Prices ex location, excluding VAT.

The [General Terms and Conditions of Delivery](#) of the Austrian Association of the Machine and Steel Construction Industry apply.

We only sell under retention of title, the goods remain our unrestricted property until they have been paid for in full.

Price changes and errors excepted.

\* Monthly net leasing rate, leasing period 60 months, no down payment, 5% residual value, subject to a positive credit check. The leasing conditions of [GRENKELEASING GmbH](#) apply. Valid for lessees based in Austria.