

## PRO-50 | 2-SPEED DRILLING MACHINE

PRO-50 featuring purpose designed motor and 2-speed gear box 240/480 rpm is optimized to provide appropriate speed for work with HSS cutters up to  $\Phi$  45 mm and twist drills up to  $\Phi$  23 mm. Rigid construction, optimized by means of FEA (finite element analysis) software extends tool life and enables depth of cut up to 75 mm.





Compact design along with innovative smart magnet with reduced weight make it a lightweight machine.

PRO-50 provides maximum holding power on thin materials thanks to Magnetic Field Shape Control (MFSC). The drill protects both the machine and the operator from work on too thin work piece by means of Magnetic Power Adhesion Control (MPAC).

PRO-50 is also equipped with Energy Saving Base (ESB) that uses only 50% of its power when motor is not running.

### Features and benefits:

- Compact design with excellent ratio weight/power
- Purpose designed motor
- Motor Speeds 240/480 rpm (under load)
- Spindle equipped with MT2
- Innovative smart magnet with reduced weight
- Rigid design to extend tool life
- Large stroke enables the use of long tools
- Motor cable with additional protective cover
- Magnetic Field Shape Control (MFSC) provides maximum holding power on thin materials
- Magnetic Power Adhesion Control (MPAC) detects adhesive force of electromagnetic base and protects both the machine and the operator from work on too thin work piece
- Energy Saving Base (ESB) uses only 50% of its power when motor is not running



## ■ New mid-range drill family at your service

Promotech is introducing new family of drills that are designed for maximum milling/drilling performance.


Customers can choose from 6 models with various tool holders including:

- Thread 1/2"
- Weldon 19,05 mm (3/4")
- Morse Taper #2.

These new drills are optimized for work with HSS cutters, TCT cutters or twist drills.



## ■ Best practices and new ideas



**Increased productivity and extended tool life**

The right choice of drilling machine for a specific application can increase process productivity and extend tool life, especially when drilling a large number of holes of the same size.

The design of the new drills is based on well proven electric motor successfully used for many years in the PRO-40 drilling machines.

Most of the components are common between the new models, which allows for flexibility in production, shorter delivery times and immediate response to market demand for specific versions of new drills.

All drills are equipped with smart electromagnetic bases including many advanced systems.

Magnetic power adhesion control module (MPAC) detects adhesive force and protects both the machine and the operator from work on too thin work pieces.

Magnetic field shape control system (MFSC) provides maximum holding power on thin materials.

Energy Saving Base (ESB) uses only 50% of its power when motor is not running.

Compact design allows the operator to drill very close to side wall and corners.



Drilling capacity up to 16 mm (0.63")  
 - with cylindrical shank twist drill in use  
 Drilling capacity up to 23 mm (0.91")  
 - with MT2 shank twist drill in use



Out of position drilling



Milling capacity up to 55 mm (2.17")  
 Depth of cut up to 75 mm (3")



Starting point of milling up to 50 mm (2")  
 below a level of a drill base

**Features and benefits of new mid-range drill family:**

- Wide selection of 6 models tailored to certain drilling applications
- Purpose designed motor proven for many years in the PRO-40 drill
- Heavy duty gear boxes optimized to match the appropriate speed of specific tools in use
- Innovative smart magnet with reduced weight
- Compact design with excellent ratio weight / power
- Various tool holders
- Rigid design to extend tool life
- Magnetic Field Shape Control (MFSC)
- Magnetic Power Adhesion Control (MPAC)
- Energy Saving Base (ESB)

**Possible tool configurations of PRO-50**



HSS cutters up to  $\Phi$  45 mm




TCT cutters up to  $\Phi$  50 mm  
 with AMT2-C19/2-3 arbor D.O.C. up to 75 mm



Starting point of drilling up to 50 mm below level of  
 a drill base with 100 mm long cutter



Adapter MT2 x 1/2" 20 UNF, Drilling chuck 1/2" 20 UNF  
 Twist drills up to  $\Phi$  16.0 mm (DIN 338)



Adapter MT2 x 1/2" 20 UNF, Quick change drilling chuck 1/2" 20 UNF  
 Twist drills up to  $\Phi$  16.0 mm (DIN 338)



### PRO-50 TECHNICAL SPECIFICATION

Motor Speeds (under load)	240/480 rpm
Power	1150 W
Weight	15,5 kg (34.17 lbs)
Max milling capacity TCT/HSS	50/45 mm (1.97"/1.77")
Max drilling capacity	23 mm (0.91")
Stroke	160 mm (6.3")
Max depth of cut	50 mm (2") 75 mm (2.95") option
Voltage	1~ 220-240 V, 50-60 Hz 1~ 110-120 V, 50-60 Hz
MFSC (Magnetic Field Shape Control)	yes
MPAC (Magnetic Power Adhesion Control)	yes
ESB (Energy Saving Base)	yes
Magnetic clamping force (surface with the thickness of 25 mm and roughness Ra = 1.25)	1009 kgf (9900 N)
Magnet base dimensions	84 mm × 168 mm × 48 mm (3.3" × 6.6" × 1.9")
Min. work piece thickness	6 mm (1/4")
Spindle	MT2
Tool holder	19 mm (3/4") Weldon
Product Code 220-240 V, 50-60 Hz	WRT-0684-10-20-00-0
Product Code 110-120 V, 50-60 Hz	WRT-0684-10-10-00-0



Drilling capacity up to 23 mm (0.91")




Milling capacity up to 50 mm (2")  
Depth of cut up to 75 mm (3") - option

#### Standard shipping set:

- Drilling machine
- Plastic box
- Handle (3pcs)
- MT2 arbor with 19 mm (3/4") Weldon tool holder
- Safety strap
- Cooling system
- Protective spring for cooling system hose
- MT2 drift
- 2.5 mm hex wrench
- 5 mm hex wrench
- 5 mm hex wrench with a handle
- 8 mm combination wrench
- Operator's manual

#### Selected additional accessories:

- PDS-0110-03-00-01-0 Pipe attachment DMP 251 for pipes with diameters of 80-250 mm (3-10")
- PDS-0111-03-00-01-0 Pipe attachment DMP 501 for pipes with diameters of 150-500 mm (6-20")
- TRZ-000008 Adapter MT2 x 1/2" 20 UNF
- UCW-000059 Drilling chuck 1/2" 20 UNF x 1.5-13 mm
- UCW-000061 Drilling chuck 1/2" 20 UNF x 3-16 mm
- UCW-0220-00-00-00-4 Arbor AMT2-C19/2-3 for 75 mm (3") depth cutting
- UKL-0440-16-00-00-0 Pressure cooling system
- PDS-0587-10-00-00-0 Vacuum pad
- AGR-0541-10-20-00-0 (230 V CEE) Vacuum pump
- AGR-0541-10-10-00-0 (115 V UK) Vacuum pump
- ZSP-0587-11-00-00-0 Compressed air ejector



Pipe attachment DMP 251



Pipe attachment DMP 501



Adapter MT2 x 1/2"



Drilling chuck



Arbor AMT2-C19/2-3



Pressure cooling system



Vacuum pad



Vacuum pump



Compressed air ejector



Your local dealer:



Vertrauen Sie auf bald 80 Jahre Erfahrung!


Die Firma **Hesse + Co** wurde 1947 als Hersteller von Blechbearbeitungsmaschinen gegründet. Seit 1980 sind wir auf den Handel mit neuen sowie gebrauchten Blechbearbeitungs- und Werkzeugmaschinen spezialisiert.

Wir haben ständig etwa 300 Maschinen in unserer 2.000 m<sup>2</sup> großen Ausstellungshalle, die nur 20 Minuten vom internationalen Flughafen Wien entfernt ist.

Trust in nearly 80 years of experience!

*Hesse + Co was established in 1947 as a manufacturer of sheet metal working machines. Since 1980 we are specialized in dealing with new and second hand sheet metal processing machines and machine tools. We always have approximately 300 machines available in our 2.000 m<sup>2</sup> showroom, which is located only 20 minutes from the Vienna International Airport, waiting for your inspection.*

[www.hesse-maschinen.com](http://www.hesse-maschinen.com)



**Öffnungszeiten:**

Mo - Do 7:45 - 16:30 Uhr  
Fr 7:45 - 13:15 Uhr

**Hesse + Co Maschinenfabrik GmbH**  
Industrienzentrum NÖ-Süd  
Straße 4 - Objekt 8  
A-2351 Wiener Neudorf  
AUSTRIA

**hesse** **hesse+co**  
*blechpower*  
maschinen und werkzeuge

Tel.: +43/2236/638 70-0  
[office@hesse-maschinen.com](mailto:office@hesse-maschinen.com)  
[www.hesse-maschinen.com](http://www.hesse-maschinen.com)

Technische Änderungen, Irrtum und Druckfehler vorbehalten.  
Gültig bis auf Widerruf.